FORTEX®



**REFERENCIA**

441537000

**CÓDIGO EAN**

8423640965294

**ARTÍCULO**

FTX-40-TEC SPRO * 400V/F3

**DESCRIPCIÓN**

High precision milling drill equipped with silent gearbox and automatic spindle advance. It incorporates thread function, tiltable table ±45o and speed change via levers. It has turn inverter, electromagnetic clutch and cooling system. Manufactured in accordance with CE standards to ensure optimal safety and performance.

FORTEX®



REFERENCIA

441537000

ARTÍCULO

FTX-40-TEC SPRO * 400V/F3

| DATOS TÉCNICOS | |
|---|---|
| **Alimentación** | 400V/F3 |
| **Potencia** | 0.85/1.5 - 1.1/2 Kw-Hp |
| **Transmisión** | Engranajes |
| **Número de velocidades** | 18 |
| **Velocidad** | 50 - 1450 m.p.m. |
| **Capacidad máxima broca** | 40 mm. |
| **Capacidad de roscado** | M24 |
| **Distancia portabrocas-columna** | 350 mm. |
| **Cono morse** | MT4 |
| **Profundidad taladro** | 180 mm. |
| **Tamaño ranura en T** | 2X18, 2X18 mm. |
| **Distancia husillo-base** | 1210 mm. |
| **Distancia husillo-mesa** | 770 mm. |
| **Recorrido máx. mesa de trabajo** | 560 mm. |
| **Diámetro columna** | 160 mm. |
| **Dimensión base** | 730X500 mm. |
| **Dimensión mesa** | 560X560 mm. |
| **Inclinación mesa** | 45º |
| **Avance husilo** | 0.10/0.20 mm./r |
| **Equipo refrigeración** | SI |
| **Altura total** | - mm. |
| **Peso Neto/Bruto** | 465 / 550 Kg. |
| **Dimensiones** | 2290X630X1090 mm. |